



MATERIALI TECNICI PER L'INDUSTRIA

GIMAS s.r.l.
 Via V.Bachelet, 23/25 - Loc. Crocetta
 29027 S.Polo di Podenzano (PC)
 Tel. 0523-558466 (2 linee r.a.) - Fax 0523-558488
 Web: www.gimas.it - Email: info@gimas.it

GIMAMID 900 POM C

MANICOTTI diametro in mm – peso Kg/m

Diametri interni																					
D. esterni	15	20	25	30	35	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	210
25	0,53																				
30	0,85	0,66																			
35	1,30	1,11	0,87																		
40		1,56	1,32	1,02																	
45		2,07	1,82	1,52																	
50		2,63	2,38	2,08	1,72																
55					2,41																
60			3,75	3,45	3,09	2,68	1,68														
65				4,24		3,48															
70				5,04		4,28	3,29	2,07													
80				6,81		6,05	5,06	3,84													
90						8,05	7,32	6,13	4,71												
100						10,52	9,56	8,37	6,95	5,30											
110							12,03		9,42	7,77											
120								13,84		10,81											
125										12,25		8,31									
130								16,78			11,90	9,81									
140											15,08	13,00	10,67								
150										20,34		16,40		11,52							
160										24,31		20,40									
170												24,27			16,66						
180									33,92			28,38	26,08	23,54		17,78					
200															30,06						
210																	23,87				
220																	28,68	25,24			
230									52,97									31,67			
250										70,80											
260																					
280																				42,69	
300											99,76										46,50
310															99,00						

Lunghezza standard: 1000 mm.

Possibile anche 3000 mm.

A richiesta fornibili anche in Gimamid 900 nero, Gimamid 1400, Gimamid 1400

Nero e Gimamid 1400T.

A richiesta si possono produrre misure sopra non elencate.